

ADDITIONAL REQUIREMENTS

1. Contractor or owner is responsible for keeping streets free from mud, stone and construction debris.
2. Construction Debris-All debris related to alterations, additions or new construction shall be deposited in a container and removed periodically as conditions warrant.
3. New York State Uniform Fire Prevention & Building Code applies.
4. No construction is allowed over or under Utility Company lines, Pipeline Company transmission line or septic systems.
5. Contractors to furnish Certificates of Insurance for Workmen's Compensation coverage to the Village of Akron. ACCORD forms are no longer acceptable proof? Please notify agent that a C-105.2 form is necessary.
6. Owners performing construction themselves must sign an Affidavit of Exemption from showing proof of Worker's Compensation insurance.
7. If metal siding is used, it must be grounded.
8. Ridge and soffit vents are required on all heated buildings.
9. Roof-Asphalt shingles to be a minimum 235#, Fiberglass 215# both with 13# left.
10. Roof-maximum two layers and structure design to carry 50 lbs. per square feet of snow load.
11. All windows to be thermal pane, including basement.
12. Every bedroom and basement with habitable space shall have at least one emergency and escape with an opening of a minimum of 5.75 square feet.
13. Chimneys to extend 2 feet above nearest roof line within 10 feet.
14. Insulation is required in hollow areas of framing, in corners and where interior portions attach to exterior walls.
15. Amount of insulation is to be determined by the amount of glazing and type of heat.
16. Construction or modification of places of public assembly will be subject to New York State Uniform Fire Prevention and Building codes.
17. Design specifications must withstand 80 mph wind.
18. This permit may be subject to requirements for making facilities handicap accessible.
19. Upon completion, to comply House numbers must be 4" in height and visibly posted on dwelling.